

KARTA KATALOGOWA

Nazwa: Obudowa IP21-IP23-IP31-IP43 dla transformatorów

Typ: EG-CR-A-IP



Poziom izolacji 12-17,5-24 kV

Typ	Moc	Stopień ochrony	Wymiary zewnętrzne (A x B x H) [mm]	Waga [kg]
EG-CR-A-IP21-31-type1	160 – 315 kVA	IP21-31	1850 x 1100 x 1560	150
EG-CR-A-IP23-type1	160 – 315 kVA	IP23	1850 x 1100 x 1560	150
EG-CR-A-IP43-type1	160 – 315 kVA	IP43	1850 x 1100 x 1560	150
EG-CR-A-IP21-31-type2	400 – 500 kVA	IP21-31	1900 x 1100 x 1760	160
EG-CR-A-IP23-type2	400 – 500 kVA	IP23	1900 x 1100 x 1760	160
EG-CR-A-IP43-type2	400 – 500 kVA	IP43	1900 x 1100 x 1760	160
EG-CR-A-IP21-31-type3	630 – 800 kVA	IP21-31	2050 x 1150 x 1960	180
EG-CR-A-IP23-type3	630 – 800 kVA	IP23	2050 x 1150 x 1960	180
EG-CR-A-IP43-type3	630 – 800 kVA	IP43	2050 x 1150 x 1960	180
EG-CR-A-IP21-31-type4	1000 – 1600 kVA	IP21-31	2300 x 1250 x 2500	230
EG-CR-A-IP23-type4	1000 – 1600 kVA	IP23	2300 x 1250 x 2500	230
EG-CR-A-IP43-type4	1000 – 1600 kVA	IP43	2300 x 1250 x 2500	230
EG-CR-A-IP21-31-type5	2000 – 2500 kVA	IP21-31	2500 x 1310 x 2650	250
EG-CR-A-IP23-type5	2000 – 2500 kVA	IP23	2500 x 1310 x 2650	250
EG-CR-A-IP43-type5	2000 – 2500 kVA	IP43	2500 x 1310 x 2650	250
EG-CR-A-IP21-31-type6	3150 kVA	IP21-31	2750 x 1400 x 2850	320
EG-CR-A-IP23-type6	3150 kVA	IP23	2750 x 1400 x 2850	320
EG-CR-A-IP43-type6	3150 kVA	IP43	2750 x 1400 x 2850	320

